



Solid Sheet

“Protect Your Investment”

Synthetic Multi Vehicle Transmission FLUID

True Brand® Transmission FLUID is a full *synthetic* automatic transmission fluid formulated to be suitable for use as a Service-Fill ATF for Asian step-automatic transmissions calling for Toyota T-III and Toyota T-IV, Honda Z-1, Nissan Matic D and Matic J and Mitsubishi SP-II and SP-III performance. True Brand® Transmission FLUID also meets the requirements of JASO 1A and other Asian OEM's like Hyundai, Subaru and Mazda. Suitable for use in automatic transmissions calling for GM DEXRON® III G/H, DEXRON VI®, Ford MERCON V® and Allison C-4. In addition, True Brand® Transmission FLUID meets the requirements of European OEM's such as ZF-TE-ML-14A, Voith 55.6335, MAN 339 Type Z-1 and MB, VW and BMW 4-and 5- speed automatic transmission specifications.

Truth - Application / Directions

- Not Recommended for use in Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT).
- **Please see Solid Application Chart.**

Truth - Features / Benefits

For more information please reference our **Solid Application Chart.**

- Performance demonstrated in standard industry and OEM tests
- Superior anti-shudder performance and durability
- Superior anti-wear protection.
- Superior clutch-shifting characteristics
- Superior oxidation control
- Superior friction performance

TYPICAL PROPERTIES

API Gravity ASTM D4052 35.1

Viscosity

@ 40°C, cSt ASTM D445 37.0

@ 100°C, cSt ASTM D445 7.2

Viscosity Index ASTM D2270 162

Brookfield Viscosity ASTM D2983

cP @ -40°C 14,200

Flash Point, °C 180

Pour Point, °C ASTM D97 -42

Color ASTM D1500 Red



T4F32



T4F128

Part # T4F32 / T4F128

12 ea / 32 oz - 4 ea / 4 gall

Also Sold in 5 gallon and 55 gallon (ask for details)

Part # T4F05 / T4F55

5 gall / 55 gall